

THERMOBILE®

BA/ES ELECTRIC HEATERS



Member of  the Honing Beheer Group of Companies

www.thermobile.co.uk

PRODUCT SPECIFICATIONS



ES 2.8

BA 9

BA 15

BA 24

WORKING PRINCIPLE

- Built-in thermostat
- Stainless steel elements
- 100% Clean and dry heat
- Fixed outlet temperature approx. 30-60 °C
- Selector switch for continuous frost protection with ventilation or space heating

FEATURES

- Frame suitable carrying
- Comfortable heat
- Suitable for closed areas
- Can be used instantly where power is available
- Good heat distribution
- Easy access for cleaning

APPLICATIONS

Building Industry

- Heating and drying out rooms, often in conjunction with a dehumidifier

Industry

- Heating of offices, canteens, stores, warehouses etc.

Livestock

- Heating poultry houses

Horticulture

- Heating of sorting areas and greenhouses

Agriculture

- Heating of livestock areas, dairy parlours, workshops and packing sheds



electricity

TECHNICAL SPECIFICATIONS | DIMENSIONS AND WEIGHTS

1 kW = 860 kcal/hr 1 kW = 3,413 Btu/hr 1 kW = 3.6 MJ/hr 1 kg = 1.2 l/hr

MODEL BA	ES 2.8	BA 9	BA 15	BA 24
Product number	98.088.002	98.088.003	98.088.004	98.088.005
Heat output (Btu/hr)	9,554	31,000	51,000	81,900
Heat output (Kw/hr)	2.8	9	15	24
Power supply (V)	230	400	400	400
Power consumption (A)	12.8	13.2	22.3	35.7
Temperature ΔT (°C)	23	32	26	30
Air flow (m³/St)	400	850	1,700	2,400
230 V plug	*			
400 V / 16 A plug		*		
400 V / 32 A plug			*	
400 V / 63 A plug				*
Thermostat built-in	*	*	*	*
Hand grip	*	*	*	*
Product dimension L x W x H (mm)	255 x 278 x 410	403 x 345 x 500	510 x 410 x 560	510 x 410 x 560
Package dimension L x W x H (mm)	273 x 333 x 436	410 x 370 x 510	590 x 450 x 570	590 x 450 x 570
Product weight (kg)	4	7	13	19
Package weight (kg)	5	8	14	20