# **THERMOBILE**





# ProHeat Cabinet oil fired with flue connection and built in fuel tank option *Erp 2018 Compliant*

#### **FEATURES**

: Capacities of 30 and 100 kW net, with an efficiency of 92%

:Plug- and- play principle, quick and easy to install.

:Standard model Four adjustable outlets equal air distribution and connection for air duct.

:Swivel head models available with 2 x adjustable swivel heads

 $: Combustion \ chamber \ and \ heat \ exchanger \ of \ heat \ resistant \ steel.$ 

: Control panel fitted with fan only facility, warning lights and built in thermostat.

#### **APPLICATIONS**

**AUTOMOTIVE**: Heating garage workshops, valeting bays,

commercial workshops.

AGRICULTURE: Heating workshops.

**INDUSTRY:** Heating and frost protection of warehouses,

halls, transit sheds.

#### **TYPES OF FUEL**

35 sec heating oil, red diesel 28 sec heating oil, kerosene

#### **Advantages of THERMOBILE PROHEAT series:**

Low-noise radial fan. ● Large air volumes guarantee quick heating. ● Standard equipped with thermostat.

### technical information

				Al	PPROX.FU	EL	HEATED	CAPACITY	POWER	FLUE		
Model	Part Number	MAX. NETT HE	AT OUTPUT	co	ONS. OIL		AIRFLOW	FUEL TANK	CONSUMPTION	CONNECTION	THERMOSTAT	INTEGRAL
		Btu/hr	Kw		L/hr	KG/hr	M3/hr	LTR	230V/400V (AMPS)	Ø MM	CONNECTION	TANK
ProHeat 30	98.087.300 ERP	104,000	30		3,4	2,8	1,900	55	2.8	120	YES	BUILT-IN
ProHeat 60	40.296.000 ERP	204,061	60.1		7,2	6,0	4,500	75	5.9	150	YES	BUILT-IN
ProHeat 100	98.087.607 ERP	333,352	97.7		10,5	7,9	8,800	100	4.6 (400V)	180	YES	OPTIONAL
ProHeat 30 SH	98.087.300 SH	104,000	30		3,4	2,8	1,900	55	2.6	120	YES	BUILT-IN
ProHeat 60 SH	40.296.000 SH	204,061	60.1		7,2	6,0	4,500	75	5.9	150	YES	BUILT-IN
ProHeat 100 SH	98.087.607 SH	333,352	97.7		10,5	7,9	8,800	100	4.6 (400V)	180	YES	OPTIONAL

TECHNICAL SPECIFICATIONS (dimensions and weights on back page)

www.thermobile.co.uk

## **ACCESSORIES**

#### <u>Swivel heads</u>

PRO HEAT 30	Swivel head kit	98.087.844
PRO HEAT 60	Swivel head kit	98.087.498
PRO HEAT 100	Swivel head kit	98.087.825



#### **Fuel tank**

PRO HEAT 100	Integral fuel tank	98.087.608
PRO HEAL 100	integral fuel tank	98.087.608




#### **Timer thermostat**



#### Flue kits

PRO HEAT 30	Flue kit	98.087.094		
PRO HEAT 60	Flue kit	98.087.095		
PRO HEAT 100	Flue kit	98.087.096		

Note: Flue kit gives 4.6 m clearance measuring from floor level




#### Flue components

PRO HEAT 30 & 60	1 m flue pipe	41.900.821		
PRO HEAT 30 & 60	45 elbow	41.900.825		
PRO HEAT 100	1 m flue pipe	41.910.212		
PRO HEAT 100	45 elbow	41.910.229		




#### PROHEAT SWIVEL HEAD RANGE



Size mm	Pro Heat 30	Pro Heat 60	Pro Heat 100
Α	500	540	760
В	1020	1120	1400
С	1600	1700	2000
D	1240	1320	1580
E	1780	1850	2230
Ø Flue	120	150	180
F			2277
G			2507

#### PRO HEAT STANDARD RANGE



NOTE PROHEAT 30 & 60 INCLUDE A BUILT IN TANK PROHEAT 100 TANK IS OPTIONAL FITTED UNDER THE HEATER

#### THERMOBILE UK LTD

12 Buckingham Close Bermuda Industrial Estate Nuneaton CV10 7JT 02476357960