



ENERGYTENDER

The EnergyTender is a high quality KIWA certified tank (IBC) and can be obtained in 995, 2000 and 3000 litres. Due to its robust design the EnergyTender is able to withstand rough handling. The lockable pump room cabinet provides protection against theft. After use the EnergyTender can be stacked to save space. The EnergyTender is ideal for the rental business.

- The EnergyTender comes in three versions. There is always an IBC that meets your specific needs!
- The EnergyTender can easily be mounted onto a trailer.
- The EnergyTender can be delivered in any RAL colour so that it seamlessly fits with your corporate identity.
- The EnergyTender meets current VLG / KIWA and ADR regulations. That means that this tank may be used anywhere on location.

FEATURES OF THE ENERGYTENDER

- 2½" fill and 1½" level opening with brass cap.
- 1 x 1" suction pipe capped.
- 1 x 2" and 1 x 1" spare connection points with caps.
- Venting with outflow restrictor.
- Forklifts slots and 4 lifting eyes.
- 1 cover (995), split cover (2000/3000).
- Mechanical contents gauge.
- 2x suction pipe ½" and 2x return connection ½" with ball valve.
- 4 way liftable.
- Fully stackable during transport.
- KIWA certified.

TECHNICAL SPECIFICATIONS | DIMENSIONS AND WEIGHTS

1 kW = 860 kcal/h 1 kW = 3,413 Btu/h 1 kW = 3.6 MJ/h 1 kg = 1.2 l/h

MODEL	Capacity (litre)	Length (cm)	Width (cm)	Height (cm)	Weight empty (kg)	ITEM NUMBER
EnergyTender 995 NLC	995	156	120	130	465	99.999.995
EnergyTender 2000 NLC	2,000	219	120	150	860	99.992.000
EnergyTender 3000 NLC	3,000	309	120	150	1,200	99.993.000



Connections.



Leak detector.



Level indicator.



Rain cap for Multitank.



Tank trolley.



Connection kit for connecting multiple Multitanks.



Oil suction set Multitank.

MULTITANKS

Multitanks are TÜV certified double-walled fuel tanks. They are available in two sizes, 700 and 1000 litres. The Multitank is equipped with a metal outer tank and a plastic inner tank and is equipped with 2" connections and a leakage indicator. For linking various Multitanks there is a connection set available. In case of outdoor installation we recommend the optional lockable rain cover. For local transport the Multitank trolley is available.

FEATURES OF THE MULTITANKS

- Double-walled.
- Plastic (HDPE) inner tank (no rust).
- Metal outer tank with 100% bund.
- Both sizes have the same footprint.
- Easily connectable.
- 2" female thread connections.
- Level meter.
- Leak detector.
- TÜV certified.

TECHNICAL SPECIFICATIONS | DIMENSIONS AND WEIGHTS

1 kW = 860 kcal/h 1 kW = 3,413 Btu/h 1 kW = 3.6 MJ/h 1 kg = 1.2 l/h

MODEL	Capacity (litre)	Length (cm)	Width (cm)	Height (cm)	Weight empty (kg)	ITEM NUMBER
Multitank 700	700	114	73	119	62	99.999.700
Multitank 1000	1,000	114	73	163	81	99.999.701
Trolley*		104	145	25	82	99.099.100

* Unmounted and packed.

FUEL ACCESSORIES

	Multitank 700 litres	Multitank 1000 litres	ITEM NUMBER
Connection kit for connecting multiple Multitanks.	*	*	99.999.703
Oil suction set Multitank.	*	*	99.999.707
Tank heating Multitank.	*	*	99.999.717
Rain cap for Multitank	*	*	99.999.820
Tank trolley	*	*	99.099.100