

# LX

## Suspended Warm Air Unit Heater Natural Gas & LPG Fired Options



### Overview

The ErP 2021 compliant suspended LX range of unit heaters which benefits from the same design as the popular LNVx range its entire construction, performance, and aesthetics, finished with the popular epoxy powder RAL 7015 stove baked paint.

Our most advanced LX is ergonomically designed with low NOx levels which provides efficient and cost effective heating solutions for any industrial and commercial properties whilst built with heating engineers in mind..

### Models Available

- LX F - Axial Fan Crossflow Units
- LX C - Centrifugal Close Coupled Fan Units
- LX V - Axial Fan Downflow Units
- LX D - Ducted No Fan Unit
- LX Duo - Axial Fan Bi-Directional Units

### Product Features

- Wide range of sizes, twelve capacities from 15 to 140kW
- Standard axial fan heater throws up to 45m.
- Compact space saving dimensions, designed to be room sealed or power flued with vertical or horizontal options
- Most comprehensive model range including Axial Fan, Centrifugal Fan ( with or without fan plenum), Axial fan downflow, Bi-Directional and Duct Package.
- Low NOx and high energy output with highest efficiency without condensing, simple and efficient high - low burner control.
- Designed for strength, rigidity and long service life with minimal noise levels.
- 409 and 316 stainless steel heat exchanger upgrades available for harsh environments.

### Specification

- LX heat exchanger will be manufactured as standard from aluminised steel tube with swaged and expanded connections into a combustion gas collection box, no welding is used to minimise stress on components.
- The four pass tubular heat exchanger can be specified with upgrade to 409 and 316 stainless steel.
- Individual in shot burners per heat exchanger tube to be fitted with Resistohm Helical Low NOx inserts capable of maximum continual 1300°c operation.
- Heaters will be capable of use with G20 Natural Gas or G31 LPG with injector change.
- LX will be supplied with a modulating gas valve assembly as standard
- To achieve designed coverage and throw the supply fan airflow will remain constant through the modulating operation.
- The casing will be designed for rigidity and low noise, anti-vibration mounts will be utilized to secure the main fan assemblies.
- There will be six top suspension points for ease of installation and additional security.
- Units will be complete with easy access swing out burner wiring panels.
- NOx Levels will be less than 70mg/kWhr.
- Heater casing will be protected by epoxy powder coat stove baked paint RAL 7015.
- Controlled by Powrmatic MC200 Optimised Start Control.



# Technical Performance

LX

Model			15	20	25	30	35	40	50	60	70	90	120	140		
Output (nominal)	High Fire (max)	kW	15.0	20.5	25.3	30.1	33.5	39.9	49.1	59.1	69.8	88.4	119.2	138.3		
	Low Fire (min)	kW	8.5	10.5	11.7	16.1	16.1	19.8	23.8	29.9	34.0	41.2	67.7	72.7		
Input (nett CV)	High Fire (max)	kW	16.2	22.2	27.4	32.1	35.8	43.1	53.6	64.2	75.3	94.9	127.0	147.5		
	Low Fire (min)	kW	8.9	11.0	12.2	16.5	16.8	20.5	25.1	31.9	35.1	43.6	70.1	75.0		
NOx Seasonal (Gross)		mg/kWh	63.8	60.0	51.7	59.0	66.8	44.4	48.3	60.2	53.9	38.7	66.8	61.2		
Seasonal Space Heating Energy Efficiency		% hs,h	78.2	78.9	79.5	80.7	80.5	80.1	79.2	79.0	80.5	79.8	79.6	80.0		
Airflow Volume	LX F & F/V & C		m³/s	0.47	0.56	0.78	0.97	1.11	1.18	1.51	1.83	1.94	2.81	3.56	3.75	
	LX D	Min	m³/s	0.42	0.56	0.78	0.97	1.11	1.18	1.51	1.83	1.94	2.81	3.56	3.75	
		Max	m³/s	0.46	0.62	0.86	1.20	1.22	1.30	1.67	2.02	2.14	3.09	3.91	4.13	
Airflow	Throw	LX F	m	10.0	14.0	20.0	23.0	28.0	30.0	35.0	38.0	42.0	44.0	45.0		
	Fan Static	LX C	Pa	220	320	220	220	200	150	250	250	250	180	290	250	
Electrics	Supply	Standard	V/ph/Hz	230/1/50												
		Optional*	V/ph/Hz	400/3/50 *on Centrifugal Units Only. 3Ph units shown in brackets ()												
	LX F	Run	amp	0.9	1.0	1.0	1.2	1.7	1.3	1.8	2.5	2.4	3.2	4.6	4.7	
		Start	amp	1.9	2.0	2.0	2.4	4.0	2.7	4.0	5.0	4.0	6.0	8.0	8.0	
	LX C	Start	amp	5.0	8.5	13.3	13.3	15.6	18.0	26.3	29(16.5)	38(18)	31.0	40(14.9)	44(16.8)	
Run		amp	2.0	3.1	4.2	4.3	4.7	5.8	7.6	10(4.8)	11(5.3)	12.8	17(4.6)	20(4.9)		
Fuel	Connection		BSP/Rc	¾"										1"		
	Nominal Inlet Pressure	Nat Gas	mbar	20.0												
		LPG	mbar	37.0												
	Consumption	Nat Gas	m³/h	1.71	2.35	2.90	3.39	3.79	4.56	5.67	6.79	7.96	10.03	13.43	15.60	
LPG		m³/h	0.66	0.91	1.12	1.31	1.46	1.76	2.19	2.62	3.08	3.88	5.19	6.03		
Mounting Height	LX F & F/Duo Crossflow	Min	m	2.5												
		Max	m	3.0					3.5							
	LX F/V Downflow	Min	m	2.5		4.0						6.0				
		Max	m	3.0		6.0				7.0				10.0		12.0
Overall Dims	LX F	Height	mm	450	500	570	670	532	720	684	760	912	810	975	1140	
		Width	mm	997	997	997	997	1325	997	1325	1325	1325	1950	1950	1950	
		Depth	mm	859	869	819	834	918	834	938	915	915	938	915	915	
Install Clearance	All	Top	mm	200												
		LH Side	mm	200												
		RH Side	mm	1000												
		Rear	mm	400												
Flue	Diameter		mm Ø	80	80	80	100	100	100	100	130	130	130	130		
	Max Length	Flue Only	m	12												
		Room Sealed	m	6												
Combustion Air Spigot			mm Ø	80	80	80	100	100	100	100	130	130	130	130		
Noise Levels	LX F	dB(A)	48	47	47	50	50	58	59	60	60	63	64	64		
	LX C	dB(A)	55	55	54	54	N/A	60	61	62	62	66	67	67		
Nett Weight	LX F	kg	59.5	73.0	76.5	81	84.0	103	122	135	149	202	238	286		
	LX C	kg	71.0	83.6	86.4	94	N/A	122	143	170	213	329	364	430		

Thermobile UK Ltd was established in 1993 as a daughter company of Thermobile Industries BV, a major European manufacturer of warm air heating products based in the Netherlands and which has been established for nearly 50 years.

## Contact Us

**Thermobile UK Limited**  
 11 & 12 Buckingham Close  
 Bermuda Industrial Estate  
 Nuneaton, Warwickshire  
 CV10 7JT

**THERMOBILE®**

Tel: +44 (0) 2476 35 79 60  
 Email: andy@thermobile.co.uk  
 Web: www.thermobile.co.uk